

MATERIAL SAFETY DATA SHEET

1 of 4

TST Holding Tank Chemical

= SECTION I - COMPOSITION / INFORMATION ON MATERIALS =

REPORTABLE COMPONENTS	CAS NUMBER	WEIGHT PERCENT
Calcium Nitrate Tetrahydrate	13477-34-4	<50%



Irritant

*All other chemical components are considered non-hazardous according to OSHA 29 CFR (1910.1200).

===== SECTION II - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: **Camco Manufacturing, Inc.**
ADDRESS: **121 Landmark Drive**
Greensboro, NC 27409

EMERGENCY PHONE: **1-800-535-5053** DATE REVISED: 05/27/2009
INFORMATION PHONE: 336-668-7661
NAME OF PREPARER: CAMCO MANUFACTURING INC.
121 LANDMARK DR.
GREENSBORO, NC 27409
1-800-334-2004

===== SECTION III - PRODUCT INFORMATION =====

PRODUCT NAME: **TST Holding tank Chemical**
NFPA CODES: Health 1
 Flammability 0
 Reactivity 0

Note - NFPA ratings are based on a 0-4 rating scale with 0 representing minimal hazards or risks and 4 representing extreme hazards or risks.

PRODUCT CODE: **40221, 40222, 40224, 40226, 40227, 40229 and 40236**

===== SECTION IV - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE: Not Determined
VAPOR DENSITY: Not Determined
SOLUBILITY IN WATER: Completely Soluble
APPEARANCE AND ODOR: Green; Fresh Fragrance
SPECIFIC GRAVITY (H₂O=1): 1.140 @ 68° F
pH (as received): 6.0 – 8.0
EVAPORATION RATE: N/A

MATERIAL SAFETY DATA SHEET

2 of 4

TST Holding Tank Chemical

===== SECTION V - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT: N/A

METHOD USED: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: Non-flammable. Use extinguisher appropriate for surrounding fire. Water, Fog or Dry Chemical.

SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS: Flush with water if involved in a fire or extreme heat.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Extreme heat could cause emission or nitrogenous fumes.

===== SECTION VI - REACTIVITY DATA =====

STABILITY: Stable

CONDITIONS TO AVOID: Excessive temperatures and strong oxidizers

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizing agents

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Nitrogen Oxide

HAZARDOUS POLYMERIZATION: Do not occur

===== SECTION VII - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Unlikely

EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

EYE CONTACT: May irritate the eyes if contact with material occurs.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

SKIN CONTACT: Frequent or prolonged contact may cause skin irritation.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

INGESTION: Swallowing large amounts may cause nausea and vomiting and may be harmful.

HEALTH HAZARDS (ACUTE AND CHRONIC): If swallowed, large amounts could be fatal.

CARCINOGENICITY: No

MATERIAL SAFETY DATA SHEET

3 of 4

TST Holding Tank Chemical

NTP CARCINOGEN: No

IARC MONOGRAPHS: No

OSHA REGULATED: No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

None known

===== SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb liquid with inert solids and shovel into containers suitable for transport and disposal. If necessary, dike spill.

WASTE DISPOSAL METHOD: Dispose of in accordance with federal, state and local regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:

Store in a cool, dry, well ventilated area.

OTHER PRECAUTIONS

None

===== SECTION IX - CONTROL MEASURES =====

RESPIRATORY PROTECTION

In well-ventilated areas, respiratory protection is not normally required.

VENTILATION: General ventilation is sufficient.

PROTECTIVE GLOVES: Wear appropriate impermeable gloves.

EYE PROTECTION: Use chemical safety glasses or goggles for eye protection.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: It is the responsibility of the user to determine the proper protective equipment that is needed based on how the product will be used.

WORK/HYGIENIC PRACTICES: Wash thoroughly after handling.

===== SECTION X - EMERGENCY AND FIRST AID PROCEDURES =====

INHALATION: Remove to fresh air. If breathing is difficult, get medical attention.

MATERIAL SAFETY DATA SHEET

4 of 4

TST Holding Tank Chemical

EYE CONTACT: Flush with large quantities of water for 15 minutes and seek medical attention.

SKIN: Remove contaminated clothing and launder before reuse. Wash skin with soap and water. Get medical attention for persistent irritation or any other symptom.

INGESTION: Induce vomiting. Dilute by giving water. Keep warm and quiet. Call physician. Do not induce vomiting or give water to anyone who is having trouble breathing, is unconscious, or having convulsions.

===== SECTION XI - 49CFR (US) Transportation Information =====

US 49 CFR DOT Shipping Description: Not Regulated
(for ground transportation with in the continental US)

===== SECTION XII - DISCLAIMER =====

To the best of our knowledge, the information contained herein is accurate, obtained from sources believed by Camco Manufacturing, Inc., to be accurate. However, the information is provided without any representation or warranty, expressed or implied, regarding its accuracy or correctness.

The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. It is the responsibility of the user to determine the safety, toxicity and suitability of his own use, handling and disposal of this product.